



Built for *Business*

Reliable productivity that keeps your business moving

The imageCLASS LBP335x is compact enough to fit effortlessly into any workspace, while fast and powerful enough to deliver a punch. With wireless connectivity, an expandable paper capacity and reliable security, productivity is made simple with the imageCLASS LBP335x.

UP TO
43 PPM
(A4)
FAST PRINT
SPEED

QUICK
6.2 SEC
FIRST PRINT
OUT TIME


WIRELESS
CONNECTIVITY

 +3
PAPER FEEDER
(OPTION)

UP TO
21,000
MONO PAGES
HIGH-YIELD
CARTRIDGE



EVERYDAY PRODUCTIVITY

Compact, wireless printer for shared office environments, delivering automatic 2-sided printing, excellent quality, and secure print confidentiality.



EASE OF USE

Configure the printer settings easily with the 5-line LCD, facilitating easy device management and maintenance.



WORKGROUP SCALABILITY

Designed for workgroups and is scalable for sharing in a department with wireless connectivity and additional paper feeders to cater for greater paper handling.



ENHANCED SECURITY

Built-in security features, system integrity checks upon startup, runtime protection and dual network support provide defense against tampering, eavesdropping, and unauthorized access.

SPECIFICATIONS

PRINT			imageCLASS LBP335x
Printing Method			Monochrome Laser Beam Printing
Print Speed	A4 ¹		43 ppm
	Letter ¹		45 ppm
	2-Sided		36 ipm (A4) / 37 ipm (Letter)
Print Resolution			600 x 600 dpi
Print Quality with Image Refinement Technology			1,200 x 1,200 dpi (equivalent)
First Print Out Time (FPOT) (Approx.) ¹²		A4	6.2 sec
Print Language			UFR II, PCL 6, Adobe® PostScript® 3™
Auto Duplex Print			Yes
Print Margins			Top/Bottom/Left/Right: 5 mm Top/Bottom/Left/Right: 10 mm (Envelope)
Supported File Format for USB Direct Print			JPEG, TIFF, PDF
Mobile Solution			Canon PRINT app, AirPrint®, Mopria® Print Service, IPP Everywhere, Microsoft Universal Print
PAPER HANDLING			
Input Tray Capacity (Plain Paper, 80 g/m²)	Standard	Cassette	550 sheets
		Multi Purpose Tray	100 sheets
	Optional	Paper Feeder	550 sheets
	Maximum		2,300 sheets (Standard + 3 Paper Feeder)
Output Tray Capacity (Plain Paper, 80 g/m²)			250 sheets
Media Size	Cassette / Paper Feeder ¹³		A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Custom (min. 105 x 148 mm to max. 216 x 355.6 mm)
	Multi Purpose Tray		A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Envelope (COM10, Monarch, DL, C5), Custom (min. 76.2 x 127 mm to max. 216 x 355.6 mm)
	2-Sided Printing		A4, Legal, Letter, Foolscap, Indian Legal, Custom (min. 210 x 279.4 mm to max. 216 x 355.6 mm)
Media Type			Plain Paper, Recycled Paper, Colour Paper, Bond Paper
Media Weight	Cassette / Paper Feeder		60 - 120 g/m²
	Multi Purpose Tray		60 - 199 g/m²
CONNECTIVITY & SOFTWARE			
Standard Interface	Wired		USB 2.0, 10Base-T/100Base-TX/1000Base-T
	Wireless		Wi-Fi 802.11b/g/n (Infrastructure Mode, Access Point, WPS)
Network Protocol	Print		LPD, RAW, IPP, IPPS, WSD-Print (IPv4, IPv6)
	TCP/IP Application Services		mDNS, DHCP, Auto IP (IPv4), DHCPv6 (IPv6), SMBv3.1.1
	Management		SNMPv3 (IPv4, IPv6), HTTP/HTTPS, SNTp
Compatible Operating System ¹⁴			Windows®, Windows Server®, macOS®, Linux, ChromeOS™
Available Software			Printer Driver
SECURITY & MANAGEMENT			
Authentication and Access Control			Department ID, PIN Login
Document Security			Encrypted Secure Print, Forced Hold Print
Network Security	Wired		IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3, Dual Network Support
	Wireless		Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE(AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE(AES)
Device Security			Verify System at Startup, Runtime Intrusion Detection with Trellix Embedded Control
Device Management			Administrator Password, Digital Certificate and Key Management, Audit Log, SIEM (Security Information and Event Management) compatibility, Security Policy Setting, Remote Management Two-factor Authentication
GENERAL			
Device Memory (RAM)			2 GB
Storage (eMMC)			32 GB (available space: 15 GB)
Display			5-line LCD
Power Requirements			AC 220 - 240 V, 50/60 Hz
Power Consumption (Approx.)	Operation		507 W (max. 1,400 W)
	Standby		6.7 W
	Sleep		1 W
Operating Environment	Temperature		10 - 30°C
	Humidity		20 - 80% RH (no condensation)
Monthly Duty Cycle ¹⁵			150,000 pages
Dimensions (WxDxH) (Approx.)			409 x 376 x 275 mm
Weight ¹⁶ (Approx.)			11.5 kg
Toner Cartridge ¹⁷	Standard		Cartridge 056: 10,000 pages (Bundled: 5,100 pages)
	Options:		Cartridge 056L : 5,100 pages Cartridge 056H : 21,000 pages
OPTIONAL ACCESSORIES			
Paper Feeder			Paper Feeder PF-C1 (550 sheets)
Barcode Printing Kit			Barcode Printing Kit- D1E

Specifications are subject to change without notice.

1* Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same. Print speed may vary depending on paper type, paper size or paper feeding direction.

2* First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.

3* The cassette may not fully close when loaded with paper longer than A4 size.

4* The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the <https://asia.canon/en/support> website when available.

5* Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

6* Excluding toner cartridge.

7* Toner cartridge yield is in accordance with ISO/IEC 19752.



Delighting You Always

SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.